Bryant Manufactured Housing R-22 Coil Ratings Sheet

OUTDOOR UNIT	MANUFACTURED HOUSING INDOOR COIL SELECTION																	
	96-8G2T-(*)P			96-8G3T-(*)P			96-8G4X-(*)P			96-8W4X-(*)P			97-8W5X-(*)P			98-8W7X-(*)P		
A/C	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR
113RNA018	13.0	17.3	NO	13.0	17.3	NO												
113RNA024	13.0	23.2	NO	13.0	23.2	NO												
113RNA030	13.0	28.0	YES	13.0	28.0	NO	13.0	28.0	NO	13.0	28.0	NO						
113RNA036	13.0	34.0	YES	13.0	34.0	YES	13.0	34.0	NO	13.0	34.0	NO						
113RNA042							13.0	40.5	YES	13.0	40.5	NO						
113RNA048										13.0	45.0	YES						
113RNA060																13.0	51.5	YES
HEAT PUMP	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR
213RN(A,G)018-A	13.0	16.9	NO															
213RN(A,G)024-A	13.0	22.0	YES	13.0	22.4	YES												
213RN(A,G)030-A	13.0	28.2	YES	13.0	28.2	YES												
213RN(A,G)036-A							12.2	33.4	YES									
213RN(A,G)042-A										13.0	40.0	YES						
213RN(A,G)048-A																13.0	45.5	YES
213RN(A,G)060-A																12.7	51.5	YES

(*) Designates either -2P for Quick Connect Fittings, -3P for Compression Fittings or -0P for Sweat Connect Fittings.

THE ABOVE MANUFACTURED HOUSING INDOOR COILS ARE EQUIPPED WITH A R-22 TXV THAT HAS AN INTERNAL CHECK VALVE FOR HEAT PUMP APPLICATIONS WHEN THAT COIL IS RATED WITH A HEAT PUMP OUTDOOR UNIT. REFER TO ARI OR THE FACTORY FOR PROPERLY MATCHED HEAT PUMP SYSTEMS. A START KIT MAY BE REQUIRED ON TXV COILS IN SHORT CYCLE SITUATIONS.

Below is a list of recommended indoor coils for use in the above applications.

INDOOR COIL MODEL	METERING DEVICE R-22	" WIDE	" DEEP	" HIGH	Coil Selections
96-862T-(*)P	TXV 1.5-3.0 TON	18	19.6	14	Fits both gas and electric furnaces. Has 1.5-3.0 Ton R-22 TXV mounted on coil.
96-863T-(*)P	TXV 1.5-3.0 TON	18	19.6	16	Fits both gas and electric furnaces. Has 1.5-3.0 Ton R-22 TXV mounted on coil.
96-864X-(*)P	TXV 2.5-5.0 TON	18	19.6	18	Fits both gas and electric furnaces. Has 2.5-5.0 Ton R-22 TXV mounted on coil.
96-8W4X-(*)P	TXV 2.5-5.0 TON	18	19.6	18.5	Fits both gas and electric furnaces, except Nordyne M3 (requires slight furnace modifications)
97-8W5X-(*)P	TXV 2.5-5.0 TON	18	19.6	20.5	Fits Mortex and Nordyne electric furnaces and Mortex Model "C" gas furnace
98-8W7X-(*)P	TXV 2.5-5.0 TON	18	19.6	24.5	Fits Mortex and Nordyne electric furnaces and Mortex Model "C" gas furnace