Nordyne Manufactured Housing Indoor Coil Ratings Sheet

	MANUFACTURED HOUSING INDOOR COIL SELECTION																	
OUTDOOR UNIT	**96-8G3T-(*)P**			**96-8G4T-(*)P**			**96-8W4X-(*)P**			**97-8W5X-(*)P**			**98-8W7X-(*)P**			**98-9W4X-(*)N****		
A/C	**SEER**	**CAP**	**TDR**	**SEER**	**CAP**	**TDR**	**SEER**	**CAP**	**TDR**	**SEER**	**CAP**	**TDR**	**SEER**	**CAP**	**TDR**	**SEER**	**CAP**	**TDR**
( )S5BD-018K	13.0	18.0	NO	13.0	18.0	NO												
( )S5BD-024K				13.0	23.8	YES												
( )S5BD-030K				13.0	29.0	YES	13.0	30.0	NO									
( )S5BD-036K				13.0	34.6	YES	13.0	35.4	NO									
( )S5BD-042K							13.0	40.0	YES	13.0	40.5	YES	13.0	41.0	YES	13.0	40.0	YES
( )S5BD-048K							13.0	45.0	YES	13.0	45.5	YES	13.0	46.0	YES	13.0	45.0	YES
( )S5BD-060K							13.0	50.0	YES	13.0	51.0	YES	13.0	51.5	YES	13.0	50.0	YES
( )S5BD-018KA				13.0	17.5	YES												
( )S5BD-024KA				13.0	23.8	YES												
( )S5BD-030KA				13.0	28.4	YES												
( )S5BD-036KA							13.0	35.6	YES									
( )S5BD-042KA							13.0	39.5	YES	13.0	40.0	YES						
( )S5BD-048KA							13.0	45.0	YES	13.0	46.0	YES	13.0	47.0	YES			
( )S5BD-060KA							13.0	50.0	YES	13.0	51.0	YES	13.0	51.5	YES			
HEAT PUMP	**SEER**	**CAP**	**TDR**	**SEER**	**CAP**	**TDR**	**SEER**	**CAP**	**TDR**	**SEER**	**CAP**	**TDR**	**SEER**	**CAP**	**TDR**	**SEER**	**CAP**	**TDR**
( )T5BD-018K	13.0	18.0	YES															
( )T5BD-024K				13.0	23.6	YES												
( )T5BD-030K							13.0	29.0	YES									
( )T5BD-036K							13.0	35.4	YES									
( )T5BD-042K							13.0	39.5	YES	13.0	40.0	YES	13.0	40.5	YES	13.0	40.0	YES
( )T5BD-048K										13.0	44.5	YES	13.0	45.0	YES	13.0	45.0	YES
( )T5BD-060K										13.0	50.0	YES	13.0	50.5	YES	13.0	50.0	YES

(*) Designates either -2P for Quick Connect Fittings or -0P for Sweat Connect Fittings and P for Plastic Pan, except -0N (see note).

**** This coil [98-994X-(*)N] is specifically designed for the Nordyne B3BV "C" cabinet Air Handler in the up flow position sometimes found in Palm Harbor Homes.**

THE ABOVE MANUFACTURED HOUSING INDOOR COILS ARE EQUIPPED WITH A TXV THAT HAS AN INTERNAL CHECK VALVE FOR HEAT PUMP APPLICATIONS WHEN RATED WITH A HEAT PUMP OUTDOOR UNIT. REFER TO ARI OR THE FACTORY FOR PROPERLY MATCHED HEAT PUMP SYSTEMS. A START KIT MAY BE REQUIRED ON TXV COILS IN SHORT CYCLE SITUATIONS.

Below is a list of recommended indoor coils for use in the above applications.

INDOOR COIL MODEL	NOMINAL SIZE METERING DEVICE R-22	" WIDE	" DEEP	" HIGH	Coil Selections
96-863T-(*)P	1.5-3.0 Ton TXV	18	19.6	16	Fits both gas and electric furnaces
96-8G4T-(*)P	1.5-3.0 Ton TXV	18	19.6	18	Fits both gas and electric furnaces
96-8W4X-(*)P	2.5-5.0 Ton TXV	18	19.6	18.5	Fits both gas and electric furnaces, slight modification required on old style Nordyne M3 gas.
97-8W5X-(*)P	2.5-5.0 Ton TXV	18	19.6	20.5	Fits Mortex & Nordyne electric furnace and Mortex Model "C" gas furnace
98-8W7X-(*)P	2.5-5.0 Ton TXV	18	19.6	24.5	Fits Mortex & Nordyne electric furnace and Mortex Model "C" gas furnace
98-994X-(*)N	2.5-5.0 Ton TXV	19.6	20.5	18.5	Specifically designed for the Nordyne B3BV "C" cabinet Air Handler in up flow position.

10/16/2006