

Nordyne Manufactured Housing Indoor Coil R-410A Ratings Sheet

OUTDOOR UNIT	MANUFACTURED HOUSING INDOOR COIL SELECTION																	
A/C	96-8G4D-(*)P			96-8W4Y-(*)P			97-8W5Y-(*)P			98-8W7Y-(*)P			98-9W7Y-(*)P			98-9W9Y-(*)P		
NORDYNE	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR
()S4BD-018KA	13.0	18.0	YES															
()S4BD-024KA	13.0	23.8	YES															
()S4BD-030KA	13.0	29.2	YES	13.0	29.4	YES												
()S4BD-036KA				13.0	36.0	YES												
()S4BD-042KA							13.0	40.0	YES	13.0	40.5	YES						
()S4BD-048KA										13.0	48.0	YES	13.0	48.0	YES	13.0	48.0	YES
()S4BD-060KA										13.0	52.0	YES	13.0	52.5	YES	13.0	53.0	YES

HEAT PUMP																		
NORDYNE	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR	SEER	CAP	TDR
()T4BD-018K	13.0	18.0	YES															
()T4BD-024K	13.0	23.6	YES															
()T4BD-030K	13.0	28.8	YES	13.0	29.2	YES												
()T4BD-036K				13.0	35.4	YES												
()T4BD-042K				13.0	39.5	YES	13.0	40.0	YES	13.0	40.5	YES						
()T4BD-048K				13.0	46.0	YES	13.0	46.5	YES	13.0	47.0	YES						
()T4BD-060K										13.0	52.0	YES	13.0	52.5	YES			

(*) Designates either -2P for Quick Connect Fittings or -0P for Sweat Connect Fittings.

THE ABOVE MANUFACTURED HOUSING INDOOR COILS ARE EQUIPPED WITH A R-410A TXV THAT HAVE AN INTERNAL CHECK VALVE FOR HEAT PUMP APPLICATIONS WHEN RATED WITH A HEAT PUMP OUTDOOR UNIT. REFER TO ARI OR THE FACTORY FOR PROPERLY MATCHED HP SYSTEMS. A START KIT MAY BE REQUIRED ON TXV COILS IN SHORT CYCLE SITUATIONS.

Part Numbers for Ordering proper TXVs Depending on Applications above	SIZE	R-22 TXV Kits (Code)	R-410A TXV Kits (Code)	Installation Code Designates which TXV letter code should be used when ordering specific coils
	1.5-3.0 Ton	R72DB0005 (T)	R72DB0003 (D)	
	2.5-5.0 Ton	R72DB0006 (X)	R72DB0004 (Y)	

INDOOR COIL MODEL	METERING DEVICE OPERATIONAL RANGE	TXV needed for size application and refrigerant type			
		" WIDE	" DEEP	" HIGH	
96-8G4D-(*)P	R410A TXV 1.5-3.0T	18	19.6	14	R410A Coil applications, fits all gas and electric furnaces
96-8W4Y-(*)P	R410A TXV 2.5-3.0T	18	19.6	18	R410A Coil applications, fits all gas and electric furnaces
97-8W5Y-(*)P	R410A TXV 2.5-3.0T	18	19.6	20.5	R410A Coil application, Nordyne & Mortex electric furnace only
98-8W7Y-(*)P	R410A TXV 2.5-5.0T	18	19.6	24.5	R410A Coil application, Nordyne & Mortex electric furnace only
98-9W7Y-(*)P	R410A TXV 2.5-5.0T	19.6	20.5	24.5	R410A Coil applications, Non-Cabinet model, sits on top of Mortex & Nordyne Electric Furnace only
98-9W79Y-(*)P	R410A TXV 2.5-5.0T	19.6	20.5	28.5	R410A Coil applications, Non-Cabinet model, sits on top of Mortex & Nordyne Electric Furnace only